

3rd Generation

Empowered by Innovation

NEC

NEC MultiSync®

EA Series

Business Desktops 19" | 22" | 24" | 27"



High-performance, LED-backlit LCD displays ideal for corporate environments

www.necdisplay.com

Reimagine your desktop computing experience.

With its 3rd generation MultiSync EA Series, NEC has developed monitor solutions that push the boundaries of what you've come to know as business-grade screen performance.

The 19" MultiSync EA193Mi, 22" EA223WM, 24" EA243WM and 27" EA273WMI deliver a completely redesigned chassis with a host of enhanced features, advanced technologies, future-proof connectivity and environmentally friendly benefits. Select models tout an IPS module, which boasts the best possible color accuracy and minimal viewing angle shift.

These models boast LED backlight technology, which not only reduces power by up to 52% compared to their predecessors, but leads to a 30% thinner and 25% lighter chassis. Other green features include ECO Mode™, a carbon footprint meter and an ambient light sensor, which automatically adjusts the brightness to the optimal setting depending on ambient lighting, screen content or both, conserving power up to 87% compared to typical energy consumption. In addition, the human sensor detects user activity in front of the monitor and reduces display power up to 95% with inactivity.

The ground breaking ControlSync™ feature allows users to control up to six select MultiSync EA Series units in a multi-monitor configuration. Upon establishing one unit as the master, you will be able to simultaneously control many performance attributes of the multi-monitor setup through the master monitor.



Highlights

- LED backlight technology provides for industry-leading low power consumption and less hazardous materials
- Four-way ergonomic stand boasts pivot, tilt, swivel and height adjustment up to 130mm to maximize your viewing comfort
- Touch-sensitive OSD® controls are integrated into the bezel, making display adjustments easier than ever
- Integrated 4-port USB 2.0 hub easily connects you to your peripherals
- Comprehensive input panel, including DisplayPort, HDMI, DVI-D and 15-pin VGA, connects you to the latest peripherals and future-proofs your investment
- Space saving, multimedia speakers, which enhance your computing experience, are hidden to maintain the monitor's aesthetic appeal (headphone jack also included)
- ControlSync enables multi-monitor setups of up to six monitors and controls up to 26 settings
- Customize Setting allows both users and IT administrators to set and restore preferred settings with just one touch, contributing to a free-seating business environment
- Smart sensing technology includes ambient light and human sensors, which considerably reduce power consumption by automatically detecting your work conditions and adjusting to the proper display brightness or entering Power Saving Mode
- Carbon footprint meter helps track and calculate the reduction of green gas emissions, while the resettable cost meter (via On Screen Display) indicates electricity cost savings based on currency settings
- NaViSet™ software offers an intuitive graphical interface, allowing for easy adjustment of display settings via mouse and keyboard. NaViSet Administrator provides all the advanced control to remotely located IT professionals.
- EPEAT Silver/Gold compliance ensures the displays reduce hazardous waste and electricity usage, resulting in lower energy costs and increased protection for the environment
- ENERGY STAR® compliance reduces electrical costs and lowers total cost of ownership

Specifications for MultiSync EA Series

MODEL	EA193Mi	EA223WM	EA243WM	EA273WMi
DISPLAY				
Panel Technology	IPS	TN		AH-IPS
Backlight Type	W-LED			
Viewable Image Size	19"	22"	24"	27"
Aspect Ratio	5:4	16:10	16:10	16:9
Native Resolution	1280 x 1024	1680 x 1050	1920 x 1200	1920 x 1080
Pixel Pitch	0.29mm	0.282mm	0.27mm	0.311mm
Pixels Per Inch	86 @ native resolution	90 @ native resolution	94 @ native resolution	82 @ native resolution
Brightness (typical)	250 cd/m ²	250 cd/m ²	250 cd/m ²	300 cd/m ²
Contrast Ratio (typical)	1000:1 (25,000: dynamic)			
Viewing Angle (typical)	178° Vert., 178° Hor. (89U/89D/89L/89R) @ CR>10	160° Vert., 170° Hor. (80U/80D/85L/85R) @ CR>10	160° Vert., 170° Hor. (80U/80D/85L/85R) @ CR>10	178° Vert., 178° Hor. (89U/89D/89L/89R) @ CR>10
Response Time (typical)	6ms	5ms	5ms	6ms
Displayable Colors	More than 16.7 million			
Synchronization Range				
Horizontal (Analog/Digital)	31.5-81.1 kHz	31.5-82.3 kHz	31.5-77 kHz	31.5-83 kHz
Vertical	56-75 Hz	56-75 Hz	56-60 Hz	56-75 Hz
Input Signal				
Video	Analog RGB 0.7 Vp-p/75 Ohms			
Sync	Separate Sync: TTL Level (Positive/Negative); Composite Sync: TTL Level (Positive/Negative); Composite Sync on Green: (0.3Vp-p negative 0.7Vp-p positive)			
Input Connectors	DisplayPort, DVI-D, VGA 15-pin D-sub	DisplayPort, DVI-D, VGA 15-pin D-sub	DisplayPort, HDMI, DVI-D, VGA 15-pin D-sub	
POWER CONSUMPTION				
On (typical)	18W	25W	29W	31W
Power Savings Mode (typical)	0.35W	0.4W	0.48W	0.48W
PHYSICAL SPECIFICATIONS				
Dimensions (WxHxD)				
Net (with stand)	16.1 x 15.2-19.5 x 8.4 in. / 408 x 386.4-496.4 x 213.9mm	19.8 x 15.1-20.2 x 8.6 in. / 503.5 x 384-514 x 218mm	21.9 x 16.1-21.2 x 9.1 in. / 556.2 x 408.9-538.9 x 230mm	25.2 x 16.5-21.6 x 9.1in / 639.3 x 418-548 x 230mm
Net (without stand)	16.1 x 13.3 x 2.6 in. / 408 x 338 x 65mm	19.8 x 13 x 2.4 in. / 503.5 x 329.7 x 60.5mm	21.9 x 14.2 x 2.5 in. / 556.2 x 359.6 x 63.8mm	25.2 x 14.9 x 2.6 in. / 639.3 x 377.8 x 66.5mm
Weight				
Net (with stand)	13.2 lbs. / 6.0 kg	12.3 lbs. / 5.6 kg	15.4 lbs. / 7 kg	15.9 lbs. / 7.2 kg
Net (without stand)	8.8 lbs. / 4.0 kg	7.3 lbs. / 3.3 kg	9 lbs. / 4.1 kg	9.5 lbs. / 4.3 kg
VESA Hole Configuration	100 x 100mm			
ENVIRONMENTAL CONDITIONS				
Operating Temperature	41-95°F / 5-35°C			
Operating Humidity	20 - 80%			
Operating Altitude	6562 ft. / 2000m			
Storage Temperature	14-140°F / -10-60°C			
Storage Humidity	10-85%			
Storage Altitude	40,000 ft. / 12,192m			
Tropical Environments	Yes			
ENVIRONMENTAL COMPLIANCE				
ENERGY STAR	6.0			
TCO	6.0	5.2	5.2	
EPEAT	Silver	Silver	Gold	
RoHS	Yes			
LIMITED WARRANTY				
	3 years parts and labor, including backlight*			
ADDITIONAL FEATURES				
	Tilt; Swivel; Pivot; Height-adjustable stand; ControlSync**; Customize Setting**; Integrated speakers; 4-port USB hub**; LED backlight; Auto brightness with ambient light sensor; Human sensor**; ECO Mode; Carbon footprint meter; Resettable cost meter; Thin frame; Carrying handle**; Rapid Response; Ambix; XtraView; Hot Key; Touch OSD controls**; OSD Lock Out; Cable management; Dynamic Visual Mode (Standard, Text, Movie, Gaming, Photo, Dynamic); NaViSet Administrator 2; VESA mount; HDCP; DDC/CI; No Touch Auto Adjust; Plug and Play (VESA DDC2B); VESA DPMS power management; AccuColor color control; Digital smoothing; Digital controls; ISO 9241-307 Class I; DICOM SIM for IPS models			
SHIPS WITH				
	Setup sheet; User manual; Power cord; 15-pin D-sub cable; DVI cable; Audio cable			

* Warranty restrictions apply. Contact your representative for details.
 **Excludes EA193Mi-BK

Touch-sensitive OSD controls**



Comprehensive input panel (select models**)



USB 2.0 hub**



4-way adjustable stand



Thin, lightweight design with integrated speakers



Ambient and human sensors**



NEC MultiSync® EA Series



Trademarks of NEC Display Solutions. All other brand or product names are trademarks or registered trademarks of their respective holders. Product specifications subject to change.
©2013 NEC Display Solutions of America, Inc. All rights reserved.
25.NEC.80.GL.UN.029 rev 06.03.2014

NEC Display Solutions

500 Park Boulevard, Suite 1100
Itasca, IL 60143
866-NEC-MORE