

ML-0650

6.5" Industrial Monitor Series



Main Features

- 6.5" VGA TFT LCD
- High brightness: 250cd/m²
- OSD Menu
- Touch panel optional
- Slim design
- Three frame options
- Supports panel/wall mounting

AUO

RoHS
RoHS compliant Product List

AMIT

Specification


System	
Input signal	RGB (VGA)
OSD Menu	Brightness, Contrast, & Position Auto Adjust
Supporting System	MS DOS, Windows®2000, Windows® XP, Linux Redhat8.0
Construction	
Frame Material	Open, steel, aluminum
Color of front frame	Black (optional)
Mounting method	Panel / Wall mounting
Size	Backside Frame: 201x151.4x46.5mm, Front Frame: 224.5x174.8x50.5mm
Packing size	
Weight	
Display	
Display type	6.5" TFT
Best Resolution	640X480
Display color	262K
Brightness	250Cd/m ²
View angle	90°(H)×50°(V)
BL MTBF	20,000 hour
Environment	
Operation temperature	0°C~50°C
Storage temperature	-20°C~+60°C
Working humidity	10%-90% RH
Power	
External AC/DC	Input: +12V@4A, Built In: +24V@1.76A
Touch panel	
Touch panel type	4 wire resistive
Resolution	2048x2048
Light transmittance	75%
Lifetime	1 million times
Operation system	MS DOS, Windows®2000, Windows® XP, Linux Redhat8.0

O: standard Δ: optional

Size	Resolution	Frame				Function						Touch Controller	
		Part No	Open	Steel	Aluminum	VGA	DVI	Vandal Glass	4 Wire TS	5 Wire TS	8 Wire TS	USB	Serial
6.5	640*480	ML-0650	O			O	Δ	Δ	Δ			Δ	Δ
	640*480	ML-0651		O		O	Δ	Δ	Δ			Δ	Δ
	640*480	ML-0652			O	O	Δ	Δ	Δ			Δ	Δ

6.5" Industrial Monitor

Outline



Part No.

Part No	Frame	Touch panel interface	Power supply
ML-0650	Open frame	USB/RS-232	+12V@4A/+24V@1.76A
ML-0651	Steel frame	USB/RS-232	+12V@4A/+24V@1.76A
ML-0652	Aluminum frame	USB/RS-232	+12V@4A/+24V@1.76A

Packing list

Items	Quantity
AC/DC +12V@5A	1
1.5 meter USB Cable	1
1.5 meter Serial cable	1
Embedded mounting buckle	4
Driver disc	1

Optional

Item	Remark
Touch panel	AMT 4wire
Touch panel	TOUCHKIT4wire
Tempered glass	2mm/ high light transmittance
DVI Signal Input	Optional