

## **Planar PLL2010MW**

20" LCD Monitor

The Planar® PLL2010MW 20" LEDbacklit LCD monitor delivers fast performance and is energy-efficient and mercury-free. The widescreen design allows less scrolling and more productivity.



SPECIFICATION	DETAIL
Product Name	PLL2010MW
Planar Part Number	997-7305-00
Viewable Size	19.5" diagonal (17.01" x 9.44")
Aspect Ratio	16:9
Contrast Ratio (typ)	1000:1
Viewing Angle (typ)	170° Horizontal and 160° Vertical
Response Time (typ)	5 ms
Brightness (Typical)	250 cd/m <sup>2</sup>
Display Type	Edge-Lit LED LCD
Display Resolution	1600 x 900
Tilt Range	-4° to +18°
Palette	16.7 million colors
Pixel Pitch	0.27 mm
Refresh Rate	56-75 Hz (60 Hz recommended)
Dimensions (W x H x D)	18.83" x 14.18" x 8.06" (478.2 mm x 360.2 mm x 204.7 mm)
Dimensions without Stand	18.83" x 11.88" x 1.97" (478.2 mm x 301.8 mm x 50.1 mm)
Panel Depth	1.97" (50.1 mm)
Display Weight	6.6 lbs (3 kgs), 5.5 lbs (2.5 kgs) without base & stand
Shipping weight	8.8 lbs. (4kgs)
Video Inputs	Analog and Digital (DVI-D w/HDCP)

<b>External Connections</b>	1 - DVI 24-pin connector; 1 - VGA D-sub 15-pin video connector; 1 - 1/8 inch audio jack
Audio Output	Integrated stereo speakers with 1W/channel
Compatibility	PC and Mac® (adapter may be required for Mac)
Power Supply	Internal
Power Consumption (max)	15W Typical, (0.5 watt Standby)
Power Requirements	AC 100/240 VAC
VESA Compatible/Location	Built-in 100 mm VESA, back
<b>Product Approvals</b>	cTUVus, CE, FCC-B, RoHS II
Service and Support	3-Year Customer First™ Warranty featuring FREE 2-Day Advance Replacement (US only)
Options / Features	Anti-glare coating, Multi-language display, On screen display (OSD), Kensington® Security Slot
In the Box	PLL2010MW 20" LCD Monitor, Power cord, VGA cable, audio cable, User's guide
UPC	8 10689 00000 6