



# Planar PT1510MX

## 15" Touch Screen Monitor

The 15" Planar® PT1510MX economical touch screen monitor with resistive touch technology is perfect for retail, POS and hospitality applications.



SPECIFICATION	DETAIL
Product Name	PT1510MX
Planar Part Number	997-3198-00
Viewable Size	15" diagonal (11.97" horizontal x 8.98" vertical)
Touchscreen Type	5-wire Resistive
Number of Touch Points	1
Touchscreen Interface	Dual Serial/USB
Transmissivity	76% (typical)
Contrast Ratio (typ)	500:1
Viewing Angle (typ)	140° Horizontal and 125° Vertical
Response Time (typ)	8 ms
Brightness (w/touchscreen)	190 cd/m <sup>2</sup>
Brightness (w/o touchscreen)	250 cd/m <sup>2</sup>
Brightness (Typical)	see Brightness w/touchscreen and Brightness w/o touchscreen
Display Type	LCD Active Matrix Flat Panel Display (TFT)
Display Resolution	1024 x 768
Tilt Range	-3° to +25°
Palette	16.7 million colors

<b>Pixel Pitch</b>	0.297 mm
<b>Refresh Rate</b>	56 to 75 Hz (60 Hz recommended)
<b>Panel Depth</b>	2.2"
<b>Dimensions (W x H x D)</b>	15.1" x 15.1" x 7.1" (383.5 mm x 383.5 mm x 180.3 mm)
<b>Dimensions without Stand</b>	15.1" x 12.3" x 2.2" (383.5 mm x 312.4 mm x 55.9 mm)
<b>Display Weight</b>	10.4 lbs (4.7 kg)
<b>Display Weight (w/o stand)</b>	7.9 lbs (3.6 kg)
<b>Shipping weight</b>	16 lbs (7.3 kg)
<b>Video Inputs</b>	Analog
<b>Audio Output</b>	Integrated stereo speakers with 1W/channel
<b>Compatibility</b>	Windows® 7, Vista, XP, 2000, ME, 98, NT 4.0, CE, XP Embedded, Apple® Mac OS, Linux, HID Compliant - no drivers needed for basic touchscreen operation
<b>External Connections</b>	DC power-in barrel connector, D-sub 15 pin, Audio In connector, D-Sub 9-pin, USB connector
<b>Power Supply</b>	External
<b>Power Requirements</b>	100-240 VAC, 50/60Hz
<b>Power Consumption (max)</b>	30W (3W standby)
<b>Operating Temperature</b>	+5° to +35° C
<b>VESA Compatible/Location</b>	Built-in 75 mm VESA, monitor back
<b>Service and Support</b>	3-Year Customer First™ Warranty featuring FREE 2-Day Advance Replacement (US only)
<b>Options / Features</b>	Anti-glare coating, Multi-language display, On screen display (OSD), Kensington® security lock function, Built-in 75 mm VESA, back
<b>Product Approvals</b>	UL/c-UL, FCC-Class B, TUV-T mark, CE, RoHS
<b>CI-Black-PN</b>	997-3198-00
<b>CI-White-PN</b>	997-3394-00
<b>In the Box</b>	PT1510MX 15" Touchscreen LCD Monitor, Power Adapter, Power Cord, VGA Cable, RS-232 Cable, USB Cable (A to B), Audio-in Cable, Driver CD, User's Guide, Quick Start Guide
<b>UPC</b>	8 10689 03198 7

For more information, please visit [www.planar.com](http://www.planar.com)

*Specifications are subject to change without notice.*

*Specification Report Date: 7/30/2015*

*© Copyright 2015 Planar Systems, Inc. All rights reserved*