

Planar PXL2470MW

24" LCD Monitor

The Planar® PXL2470MW 24" widescreen LED backlit LCD monitor features a wide viewing angle, DisplayPort and HDMI inputs, and external power supply. The Planar PXL2470MW fits seamlessly into home, office, healthcare, and digital signageenvironments.



SPECIFICATION	DETAIL
Product Name	PXL2470MW
Planar Part Number	997-7346-00
Viewable Size	23.6" diagonal (20.52" horizontal x 11.54" vertical)
Aspect Ratio	16:9
Contrast Ratio (typ)	1000:1
Viewing Angle (typ)	178° Horizontal and 178° Vertical (Specified at CR>10:1)
Response Time (typ)	5 ms (GTG)
Brightness (Typical)	250 cd/m²
Display Type	Edge-Lit LED LCD Active Matrix Flat Panel Display (TFT)
Display Resolution	1920 x 1080, full HD
Tilt Range	-5° to +20°
Palette	16.7 million colors
Pixel Pitch	0.2715 mm
Refresh Rate	55~76 Hz (60 Hz recommended)
Dimensions (W x H x D)	22.10" x 15.73" x 7.85" (561.3 mm x 399.6 mm x 199.3 mm)
Dimensions without Stand	22.10" x 13.12" x 1.58" (561.3 mm x 333.2 mm x 40.2 mm)
Panel Depth	1.58" (40.2 mm)
Display Weight	7.8 lbs (3.53 kg); Weight without stand: 7.1 lbs (3.2 kg)
Shipping weight	11.3 lbs (5.1 kg)
Video Inputs	HDMI, DisplayPort, VGA

Audio Output	1W x 2, headphone out
External Connections	HDMI 19-pin, DisplayPort 20-pin, VGA 15-pin, 3.5 mm audio in, 3.5mm headphone out
Compatibility	PC and Mac® (adapter may be required for Mac)
Power Supply	External (DC power)
Power Consumption (max)	26 Watt Typical (<0.5 Watt standby)
Power Requirements	AC 100/240 VAC
VESA Compatible/Location	Built-in 100 mm VESA, back
Product Approvals	FCC-B, CE, UL/cUL, RoHS
Service and Support	3-Year Customer First™ Warranty featuring FREE 2-Day Advance Replacement (US only)
Options / Features	Wide color consistent viewing angle, Uniform bezel, Discreet branding, Anti-glare coating, Multi-language display, On screen display (OSD), Kensington® Security Slot
In the Box	PXL2470MW 23.6" LED LCD Monitor, 12V DC AC Adaptor, Power Cord, VGA Cable, DisplayPort Cable, Audio Cable, User's Guide
UPC	8 10689 00018 1