

Planar PXL2770MW

27" LCD Monitor

The Planar® PXL2770MW 27" widescreen monitor features a wide viewing angle, DisplayPort and HDMI inputs, and external power supply. The Planar PXL2770MW fits seamlessly into home, office, healthcare and digital signage environments.



SPECIFICATION	DETAIL
Product Name	PXL2770MW
Planar Part Number	997-7412-00
Viewable Size	27" diagonal (23.54" horizontal x 13.24" vertical)
Aspect Ratio	16:9
Contrast Ratio (typ)	1000:1
Viewing Angle (typ)	178° Horizontal and 178° Vertical (Specified at CR>10:1)
Response Time (typ)	14 ms
Brightness (Typical)	250 cd/m ²
Display Type	Edge-Lit LED LCD Active Matrix Flat Panel Display (TFT)
Display Resolution	1920 x 1080, full HD
Tilt Range	-5° to +20°
Palette	16.7 million colors
Pixel Pitch	0.3114 mm
Refresh Rate	55-76Hz (60Hz recommended)
Dimensions (W x H x D)	25.33" x 17.63" x 9.43" (643.3 mm x 447.8 mm x 239.4 mm)
Dimensions without Stand	25.33" x 15.03" x 1.62" (643.3 mm x 381.8 mm x 41.1 mm)
Panel Depth	1.62" (41.1 mm)
Display Weight	10.4 lbs (4.7 kgs), 9.5 lbs (4.3 kgs) without base & stand
Shipping weight	14.4 lbs (6.5 kgs)
Video Inputs	HDMI, DisplayPort, VGA

Audio Output	1.5W x 2, headphone out
External Connections	HDMI 19-pin, DisplayPort 20-pin, VGA 15-pin, 3.5 mm audio in, 3.5mm headphone out
Compatibility	PC and Mac® (adapter may be required for Mac)
Power Supply	External (DC power)
Power Consumption (max)	36 Watt Typical (<0.5 Watt standby)
Power Requirements	AC 100/240 VAC
VESA Compatible/Location	Built-in 100 mm VESA, back
Product Approvals	UL, FCC-B, CE, cUL, RoHS
Service and Support	3-Year Customer First™ Warranty featuring FREE 2-Day Advance Replacement (US only)
Options / Features	Wide color consistent viewing angle, Uniform bezel, Discreet branding, Anti-glare coating, Multi-language display, On screen display (OSD), Kensington® Security Slot
In the Box	PXL2770MW 27" LED LCD Monitor, 12V DC AC Adaptor, Power Cord, VGA Cable, DisplayPort Cable, Audio Cable, User's Guide
UPC	8 10689 00019 8