

## e2460Swhu

























HIGH-DEFINITION MULTIMEDIA INTERPACE	ENERGY STAR SILVE
Cabinet Color	Fine Texture Black Finish
Panel	TFT Active Matrix, LED Backlight
	24" Class Widescreen, 16:9 Aspect Ratio
	23.6" Viewable Image Size, Diagonal
Pixel Pitch	0.272 x 0.272mm
Display Area	521.3mm x 293.2mm
Brightness	250 cd/m2 (typ)
Contrast Ratio	20,000,000:1 (dynamic)
Response Time	5ms (typical)
Viewing Angle	Horizontal: 170 Degrees (CR>10)
	Vertical: 160 Degrees (CR>10)
Scanning Frequency	Horizontal: 30K~83KHz
	Vertical: 50~76 Hz
Pixel Frequency	170MHz
Maximum Resolution	1920x1080x60Hz
Recommended Resolution	1920x1080@60Hz
Supported Resolutions	640x480@60/67/72/75Hz, 800x600@56/60/72/75Hz,
	1024x768@60/70/75Hz, 1280x960@60Hz, 1280x1024@60Hz,
	1440x900@60Hz, 1680x1050@60Hz, 1920x1080@60Hz
Color	16.7M
Signal Input	Analog: 0.7Vp-p(standard), 75 OHM, Positive
Digital Input	DVI & HDMI with HDCP*
Connectors	Analog RGB Signal: 15-pin D-sub Male
	Digital Signal: 24-pin DVI-D, 18-pin HDMI
Power Source	Universal 100~240VAC, 50/60Hz
Power Consumption	On: 42 Watts Max, Standby: <0.5W
Plug & Play	DDC/2B, DDC/CI
User Control	Auto/source/Exit, Eco(DCR)/-, Volume/+, Menu, Power
OSD Languages	16 Languages including English, French and Spanish
Regulations	cTUVus, FCC, ROHS, EPA 5.1, EPEAT Silver, Windows 7 Logo
Built-in Speakers	2Wx2
Other Features	USB 2.0 Hub 1x4 (1x fast charger), User Friendly Graphical OSD
	Menu, VESA 100mm Wall Mount Compliant*, Kensington Security
	Slot, , Includes AOC's e-Saver, Screen+ and iMenu Software
Dimensions (WxHxD mm)	Monitor: 565.4x402.1x219.3, Carton: 621x476x131
Dimensions (WxHxD inches)	Monitor: 22.3x15.8x8.6, Carton: 24.6x18.7x5.2
Weight	10.9 lbs (4.96 kgs) Net
- 3	13.6 lbs (6.19 kgs) Gross
Loading Qty w/pallet	20' = 648 pcs.; 40' Std = 1368 pcs.
UPC Code	685417050680
	otice *High-handwidth Digital Content Protection: Enables viewing of High-Definition contents **Wall