23" Full HD 1080p Projected Capacitive Touch Monitor

ViewSonic
See the difference

Intuitive 10-Point Touch Design

TD2340



Exceptional interactivity comes standard in the ViewSonic® TD2340 Windows® 8 certified 23" 10-point touch IPS monitor. 1920x1080 Full HD resolution with projected capacitive touch technology delivers seamless and accurate touch experience. Stunning color performance with IPS technology and 20,000,000:1 MEGA Dynamic Contrast Ratio. Integrated speakers with SRS Premium Sound® complete the multimedia package. DisplayPort®, HDMI, VGA inputs provide flexible and convenient connectivity. Dual hinge stand design ensures outstanding ergonomic comfort and productivity. Even VESA mountable design for additional convenience. The TD2340 is fully USB HID compliant and certified with Windows 8. This is the gateway to the new world of interactivity.

The New World of Interactivity

With the 10-point projected capacitive touch technology, TD2340 delivers lighting fast, responsiveness to deliver the best multi-touch experience possible. Partnered with the Windows

8 Touch Certification, TD2340 allows anyone to enjoy the best of the interactivity that Windows 8 or any other systems have to offer.



Comfort and Productivity Come Standard

The advanced ergonomic dual hinge stand makes the TD2340 the most flexible 10-point touch monitor in the market. Users can adjust the height, pivot or even lay the monitor flat, tailoring the touch experience to their preference. The TD2340 also comes with a VESA mountable design that allows for wall or display arm mounting options.



23" Full HD 1080p Projected Capacitive Touch Monitor



TD2340

Flexible Connectivity

ViewSonic has built in all the connectivity users need. The TD2340 comes with advanced DisplayPort and HDMI connectivity, VGA is also provided for more traditional applications. 2 USB ports provide additional options to connect peripherals.










Stunning Color Performance

Equipped with IPS technology panel, a 1920x1080 Full HD resolution and a 20,000,000:1 MEGA Dynamic Contrast Ratio, brilliant color performance is guaranteed. IPS technology allows super wide viewing angel and delivers accurate color reproduction. With the stunning 23" screen, TD2340 users will enjoy entertainment like never before.



ENERGY STAR® and EPEAT Gold Certified

The TD2340 is environmentally sound with energy-saving LED backlight and Eco-mode. You can save up to 40%* in your energy cost comparing to a regular 22" monitor.



Specifications		
PANEL	Type Display Area Optimum Resolution Brightness Contrast Ratio ynamic Contrast Ratio Viewing Angles Response Time Backlight Backlight Life Panel Surface	23" Wide Color TFT Active Matrix LED 20.0" horizontal x 11.3" vertical; 23.0" diagonal 1920x1080 250 cd/m² (typ.) 1000:1 (typ.) 20,000,000:1 178° horizontal, 178° vertical 7ms (typ.) White-light LED 30,000 hours (min.) 7H Scratch Resistant Surface Hardness
VIDEO INPUT	Analog Digital Frequency Sync	RGB analog (0.7 / 1.0 Vp-p, 75 ohms) HDMI (TMDS, 100 ohms) / DisplayPort (PCI-E) Fh: 24-83kHz, Fv: 50-76Hz Separate Sync
AUDIO OUTPUT	Speakers	2-watt (x2)
COMPATIBILITY	PC Mac [®]	PC compatibles (VGA up to 1920 x 1080 Non-Interlaced) Power Mac (up to 1920 x 1080)
CONNECTOR	Video Analog Video Digital USB Hub Audio Power	15-pin mini D-sub (VGA) HDMI (v1.4), DisplayPort USB x2, USB Upstream x1 Audio In (3.5mm mini-jack) Earphone Out (3.5mm mini-jack) Internal power board, 3-pin plug (CEE22)
POWER	Voltage Consumption Optimize Conserve	AC 100–240V (universal), 50 / 60Hz w/o audio 22W (typ.) / w/ audio 45W (typ.) 23W (typ.) 18.5W (typ.)
CONTROLS	Front Panel Buttons OSD	1, 2, Down, Up, Power Auto Image Adjust, Contrast/Brightness, Input Select (D-SUB HDMI, DisplayPort), Audio Adjust (Volume, Mute), Color Adjust (sRGB, Bluish, Cool, Native, Warm, User Color [R,G,B]), Information, Manual Image Adjust (H/V Position, Horizontal Size, Fine Tune, Sharpness, Dynamic Contrast,

Memory Recall

Response Time, Aspect Ratio, Eco-mode), Setup Menu (Language Select, Resolution Notice, OSD Position, OSD Timeout, OSD Background, Auto Power Off, Power Indicator),

	Rotation	90°
OPERATING CONDITIONS	Temperature Humidity	32-104° F (0-40° C) 20-90% (non-condensing)
DIMENSIONS (W x H x D)	Physical with Stand Physical without Stand Packaging	22.7 x 17.9 x 12.8 in. / 576.6 x 453.8 x 324.5 mm 22.7 x 17.9 x 2.6 in. / 576.6 x 453.8 x 66.5 mm 26.4 x 20.1 x 9.2 in. / 671 x 510 x 234 mm
WEIGHT	Net with Stand Net without Stand Gross	20.4 lb. / 9.2 kg 14.5 lb. / 6.6 kg 26.9 lb. / 12.2 kg
WALL MOUNT	VESA®	100mm x 100mm
REGULATIONS		CE, CB, BSMI, PSB, SASO, C-tick, SASO, KC, UL/cUL, FCC-B (including ICES003), Mexico Energy, GOST-R, UkrSEPRO + DOC, TCO 5.2, Erp, CCC, CEL Level1, ENERGY STAR®, EPEAT Gold, WEEE, ROHS, REACH SVHC list & DOC, Windows 7 / Windows 8
RECYCLE / DISPOSAL		Please dispose of in accordance with local, state or federal laws.
POWER MANAGEMENT		ENERGY STAR® standards / EPEAT Gold
WARRANTY		Three-year limited warranty on parts, labor and backlight.

What's in the box?

ERGONOMICS

TD2340 display, power cable, audio cable, VGA cable, HDMI cable, USB cable, Quick Start Guide, ViewSonic Wizard CD (available in some countries only)









*Energy savings may vary based on actual usage and other factors. Program, specifications and availability are subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Premium Sound and the SRS Logo are trademarks or registered trademarks of SRS Labs. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2013 ViewSonic Corporation. All rights reserved. [16679-02B-07/13]