# 24" (23.6" Viewable) Full HD LED Monitor



Ergonomic Design for Flexibility and Productivity

VG2428wm-LED



The 24" (23.6" viewable) ViewSonic® VG2428wm-LED is a Full HD LED monitor with full ergonomics and thin bezel design. With an energy efficient, higher performance LED backlit panel, the VG2428wm-LED can deliver more vibrant colors and outstanding image performance. The VG2428wm-LED is the ideal monitor to lower the total cost of ownership with its full ergonomics with pivot, height adjust, swivel and tilt to maximize comfort and productivity, and ViewSonic's proprietary Eco-mode which can save up 40%\* of power consumption. DVI and VGA connectors provide diverse input options and the 2-port USB hub gives clutter-free and convenient USB device connectivity. The slim bezel coupled with hidden stereo speakers make VG2428wm-LED a space saver. The VESA mountable design allows users to mount the monitor to the wall or any monitor stand. ViewSonic's industry leading pixel performance guarantee and 3-year limited warranty give you peace of mind in your investment.

## Full HD 1080p for Superlative Pixel Performance

The VG2428wm-LED features Full HD 1080p 1920x1080 resolution for unbelievable pixel-by-pixel image performance. You'll experience the most amazing clarity and detail whether it be for working, gaming, or enjoying the latest in multimedia entertainment. A 16:9 widescreen ratio minimizes eye fatigue even after hours of viewing and is perfectly compatible with multi-window viewing without toggling.







Normal

Full HD 1080p

# **Productivity & Comfort**

The VG2428wm-LED is one of the great examples of an ergonomically designed tool. Based on your height, chair and desk conditions, you can adjust it up and down for 5.3 inches, swivel it 360°, or tilt it 20° degrees, whatever makes you more comfortable.



# 24" (23.6" Viewable) Full HD LED Monitor



# VG2428wm-LED

# **Eco-Mode Conserves More Energy**

ViewSonic's proprietary Eco-mode function is built into all LED displays, offering options to "Optimize (65%)" or "Conserve (55%)". Both modes reduce display brightness and conserve up to 30%\* energy. Especially in a low ambient light, Eco-mode adjusts brightness and improves visibility while reducing eye fatigue and prolonging the display's lamp life. With Eco-mode, lamp replacement expenditures are reduced while practicing eco-friendliness.





## Planet-Friendly Mercury-Free LED Backlighting

LED backlighting enhances display performance, delivers an outstanding color range, and adjusts contrast ratios for remarkably detailed images. The LED backlighting further conserves up to 50%\* more energy when compared to conventional displays to allow a slimmer profile and a most pleasing entertainment experience.



Specification:	s	
LCD PANEL	Type Display Area Optimum Resolution Brightness Contrast Ratio Dynamic Contrast Ratio Viewing Angles Response Time Backlight Backlight Life Aspect Ratio Panel Surface	24" (23.6" Viewable) Wide Color TFT Active Matrix LED 20.5" horizontal x 11.5" vertical; 23.6" diagonal 1920x1080 300 cd/m² (typ) 1000:1 static (typ) 10,000,000:1 170° horizontal, 160° vertical 5ms (typ.) White-light LED 30,000 hours (min) 16:9 Anti-glare, hard-coating (3H)
INPUT	Analog Digital Sync Frequency	RGB analog (75 ohms, 0.7 / 1.0 Vp-p) DVI-D (TMDS, 100 ohms), Display Port H/V separated (TTL) Fh = 24 ~ 82 kHz; Fv = 50 ~ 75 Hz
AUDIO OUTPUT	Speakers	2-watt (x2)
COMPATIBILITY	PC Mac®	VGA up to 1920x1080 @ 60Hz (preferred) Power Mac (up to 1920x1080)
CONNECTOR	Analog Digital Audio USB Hub Power	15-pin mini D-sub (VGA) DVI-D (with HDCP) 3.5mm Audio In USB 2.0 (x2), USB upstream Internal Power Board, 3-pin plug (CEE22)
POWER	Voltage Consumption Optimize Conserve	AC 100–240V (universal), +/-10% Wide Range 32W (typ) 19W (typ) 15W (typ)
CONTROLS	Basic OSD	Power, 1, down, up, 2 Auto Image Adjust, Contrast/Brightness, Input Select (D-SUB, DVI), Audio adjust (Volume Mute), Audio Input, Color Adjust (sRGB, 9300K, 7500K, 6500K, 5000K, User Color [R, G, B]), Information, Manual Image Adjust (H/V Position, Horizontal

Size, Fine Tune, Sharpness, Dynamic Contrast, Response Time, Aspect Ratio, Eco-mode), Setup Menu (Language, Resolution Notice, OSD Position, OSD Timeout, OSD, Background, Auto Power Off), Memory Recall

ERGONOMICS	Tilt Swivel Height Adjust Pivot	Forward 5° – Back 20° 360° 5.3" (0-135mm) 0-90°
OPERATING CONDITIONS	Temperature Humidity	32–104°F (0–40°C) 10–90% (non-condensing)
DIMENSIONS (W x H x D)	Physical with stand Physical without stand Packaging	22.2 x 17.4 x 9.8 in. / 563.6 x 442.3 x 249.8 mm 22.2 x 13.2 x 2.6 in. / 563.6 x 335.2 x 66.9 mm 25.3 x 20.7 x 11.9 in. / 644 x 527 x 302 mm
WEIGHT	Net with stand Net without stand Gross	14.3 lb. / 6.5 kg 9.7 lb. / 4.4 kg 19.8 lb. / 9.0 kg
WALL MOUNT	VESA®	100 x 100 mm
REGULATIONS		UL/cUL, FCC-B / ICES-003B, TUV-s, UL COC, ENERGY STAR®, Mexico Energy, NOM, WEEE, ROHS, REACH SVHC List, CE, CB, TCO 6.0, Windows 7 / Windows 8
RECYCLE/DISPOSAL		Please dispose of in accordance with local, state or federal laws.
POWER MANAGEMENT		ENERGY STAR 6.0
WARRANTY		Three-year limited warranty on parts, labor and backlight

#### What's in the box?

VG2438wm-LED Display, power cable, VGA video cable, DVI cable, audio cable, ViewSonic Wizard CD-ROM, Quick Start Guide, Base Instruction Guide











<sup>\*</sup>Energy savings may vary based on cost, actual usage and other factors. Specifications and availability are subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Windows and Windows 8 are trademarks or registered trademarks of Microsoft Corporation in the United States and/or other countries. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2012 ViewSonic Corporation. All rights reserved. [16404-00B-10/12] VG2428wm-LED