

# VG2732m-LED

**27" WIDESCREEN LED MONITOR  
WITH PIVOT, HEIGHT ADJUST AND USB HUB**

## Connect with Green Performance.

The VG2732m-LED is one of ViewSonic's latest 27" models. Its 27" display with a native 1920x1080 resolution is big enough to replace most dual-monitor setups. What makes it even more appealing is the LED backlight for up to 50% energy savings. Monitor is also fully ergonomic with 90° pivot, height adjust, swivel and tilt. The slim bezel design coupled with hidden stereo speakers make VG2732m-LED a space saver. You can put it on your desk or mount on your wall or on any VESA® compliant monitor stand. With ViewSonic's strongest pixel performance guarantee and 3-year limited warranty, you will have peace of mind in your investment.



### GO GREEN WITH FULL POWER

- > **Uses 50% less power**  
Without compromising your viewing quality and has eco-friendly mercury-free WLED backlight.
- > **Multi-functional base design (pivot, height adjustment, swivel)**  
VESA compliant wall-mount interface and detachable base for ergonomic flexibility with 90° pivot, 5.3 height, tilt and 356° swivel adjustments.
- > **USB hub**  
4-port USB hub provides easy connectivity for USB devices.
- > **Multimedia enhanced**  
Stereo speakers provide clear and rich sound.
- > **Widescreen aspect ratio with 1920x1080 resolution**  
The widescreen aspect ratio allows you to view Full HD content in its native format with no stretching or distortion.
- > **OptiSync® digital/analog inputs expand your connectivity**  
Multi-mode input technology supports both digital (DisplayPort + DVI) and analog (VGA) signals for ultimate compatibility and configuration flexibility.
- > **Eco-mode**  
Environmentally-friendly Eco-mode reduces power consumption and extends backlight life.
- > **Stylish slim-bezel design**  
An ultra-thin bezel lets you see more without taking up valuable desktop real estate.



**VIEWSONIC**  
PRODUCTS, PROGRAMS,  
AND SERVICES


**ViewSonic®**  
See the difference® 

# VG2732m-LED

27" WIDESCREEN LED MONITOR WITH PIVOT, HEIGHT ADJUST AND USB HUB



<b>LCD</b>	Size	27" wide Color TFT Active Matrix LED
	Display Area	23.6" horizontal x 13.3" vertical; 27" diagonal
	Optimum Resolution	1920x1080
	Brightness	300 cd/m <sup>2</sup> (typ)
	Contrast Ratio	1200:1 static (typ) ; 20,000,000:1 dynamic
	Viewing Angles	170° (H), 160° (V) @ 10:1 contrast ratio
	Response Time	3ms (typ)
	Pixel Pitch	0.31mm (H) x 0.31mm (V)
	Panel Surface	Anti-Glare
	Light Source	Long life, 30,000 hrs. (typ)
Color Support	16.7 M (6-bits + Hi FRC)	
<b>INPUT</b>	Analog	RGB Analog (75 ohms, 0.7/1.0 Vp-p)
	Digital	DisplayPort and DVI-D (HDCP)
	Sync	H/V Separated
	Frequency	F <sub>H</sub> : 24-82kHz, F <sub>V</sub> : 50-75Hz
<b>COMPATIBILITY</b>	PC	VGA up to 1920x1080 non-interlaced
	Mac®*	Power Mac™ up to 1920x1080
<b>CONNECTOR</b>	Analog	15-pin mini D-sub
	Digital	DisplayPort and DVI-D
	Audio	3.5 mm Audio in
	Power	Built-in power adapter, 3-Pin plug
	USB	2.0, 1-up / 4-down
<b>AUDIO</b>	Speaker	2x2-watt
<b>POWER</b>	Voltage	AC 100–240V (Universal); 50/60Hz(Switch)
	Consumption	55W (typ), 33W (Eco-mode)
	Sleep Mode	≤1W
<b>CONTROLS</b>	Basic	Power, Mute, [1], Up [▲], Down [▼], [2]
	OnView	Auto image adjust, Contrast/Brightness, Audio adjust: Volume, mute, Color adjust: sRGB, 9300K, 7500K, 6500K, 5000K, user color [R, G, B] Information, Manual image adjust: H/V position, Horizontal size, fine tune, sharpness, dynamic contrast, aspect ratio, Eco mode, Setup menu: Language select, resolution notice, OSD position, OSD timeout, OSD background, sleep, memory recall
<b>ERGONOMICS</b>		Height adjustment range 5.3", tilt -5°/+20°, swivel range 356°, pivot 90°
<b>OPERATING CONDITIONS</b>	Temperature	41–95° F (5–35° C)
	Humidity	20–80% (non-condensing)
<b>DIMENSIONS (WxHxD)</b>	Physical with stand	25.3" x 17.0" x 9.5" (642mm x 434mm x 241mm)
	Physical without stand	25.3" x 15.4" x 2.6" (642mm x 391mm x 65mm)
	Packaging	28.7" x 20.6" x 9.5" (729mm x 523mm x 240mm)
<b>WEIGHT</b>	Net with stand	14.5 lb. (6.6 kg)
	Net without stand	11.5 lb. (5.2 kg)
	Gross	20.3 lb. (9.2 kg)
<b>REGULATIONS</b>		CB, TCO'05, WEEE, RoHS, UL/cUL, FCC-B, IRAM, NOM, EPEAT-Silver, BSMI, PSB, C-TICK, CCC, CEL, CECP, ENERGY STAR®
<b>WALL MOUNT</b>		VESA 100mmx100mm
<b>POWER MANAGEMENT</b>		Meets ENERGY STAR® standards
<b>RECYCLE/DISPOSAL</b>		Please dispose of in accordance with local, state or federal laws.
<b>PACKAGE CONTENTS</b>		LCD monitor, power cable, audio cable, USB cable, VGA cable, DVI cable, Quick Start Guide
<b>WARRANTY</b>		Three-year limited warranty on parts, labor and backlight.



ViewSonic Corporation's OMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by TUV NORD.

Sales: (888) 881-8781 • SalesInfo@ViewSonic.com • ViewSonic.com

\*Adapter may be required. Analog adapter available from ViewSonic. Specifications subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2011 ViewSonic Corporation. All rights reserved. [15628-00B-04/11] VG2732m-LED

**ViewSonic®**  
See the difference®

For more product information, visit us on the web at ViewSonic.com